PB S225-23DS 4×4

Self-propelled Scissor lift 22,30 m Working height 2,26 m Total width indoor + outdoor






Technical specifications

	Working height	22,30 m		Platform extension (scissors)	2,72 m
	Platform height	20,30 m	0/0	Gradeability	30 %
	Lift capacity	750 kg		Speed - stowed	5,40 km/h
	Lift capacity platform extension	750 kg		Speed - raised	0,51 km/h
	Total length	4,84 m	4	Drive type	Diesel-hydraulic drive
	Total width	2,26 m	-\$+	Battery capacity	180 Ah
	Total height	3,83 m		Area of application	indoor + outdoor
	Turning radius outside	4,80 m		People indoor	4
1	Transport height	2,91 m		People outdoor	4
kg	Total weight	13.090 kg		Drivable at full height	Yes

Product description

- With an immense 22.30 m working height the PB S225-23DS 4x4 is predestinated for installation, mounting and maintenance works on construction sites or in industrial areas
- For working at high altitudes the device has with 750 kg lift capacity the necessary power reserves on the entire max. 7.23 m x 2.21 m platform
- The 4-wheel-drive and the standard differential lock of the scissor ensures sufficient propulsion and the necessary balance in use at hard drivable, uneven grounds
- A fully automatic supports system levels the machine via push of the button and within seconds on uneven ground, thus provides a huge plus of stability and security
- The Hatz-Diesel engine is very powerful and allows long working cycles

Product diagram



We reserve the right to make technical changes / improvements.





PB S225-23DS 4×4

Self-propelled Scissor lift 22,30 m Working height 2,26 m Total width indoor + outdoor



Product images









We reserve the right to make technical changes $\slash\hspace{-0.6em}$ / improvements.



