

PB TOP SERIES
SCISSOR LIFTS

PLATFORMERS
BUSINESS

PB TOP 12

Working height:
49,48 ft - 73,82 ft

Platform height:
42.87 ft - 67.26 ft

Width:
4,00 ft

Drive:
Electro-hydraulic



Technical highlights in series

- No space? no problem:
Slim + extremely high
 - Auto. PB supports
system
 - Differential lock
- Emission-free & eco-
friendly & reliable



www.pblift.de



PB TOP 12 SERIES

8 types

Working height:
49,48 ft - 73,82 ft

Platform height:
42,87 ft - 67,26 ft

Width:
4,00 ft

Drive:
Electro-hydraulic



PB Liftechnik GmbH
Gewerbegebiet Gassenacker

Phone +49 (0) 90 77 - 95 00 - 0

E-Mail: info@pblift.de
Website: www.pblift.de



PB TOP 12 series	PB S151-12E	PB S151-12ES	PB S171-12E	PB S171-12ES
Operation area	Indoor	In-/outdoor	Indoor	In-/outdoor
Drive	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Working height	49,48 ft	50,20 ft	56,76 ft	56,76 ft
Platform height - raised	42,91 ft	43,64 ft	50,20 ft	50,20 ft
Drivable at full height	Yes	Yes	Yes	Yes
Drive speed stowed / raised	1,49 / 0,09 mph	1,49 / 0,09 mph	1,49 / 0,09 mph	1,49 / 0,09 mph
Platform size (l x w)	9,51 x 3,90 ft	9,51 x 3,90 ft	9,51 x 3,90 ft	9,51 x 3,90 ft
Platform size max. (l x w)	12,80 x 3,90 ft	12,80 x 3,90 ft	12,80 x 3,90 ft	12,80 x 3,90 ft
Lift capacity	1322,77 lbs	1322,77 lbs	1102,31 lbs	1102,31 lbs
Lift capacity extension	1322,77 lbs	1322,77 lbs	1102,31 lbs	1102,31 lbs
Occupancy (in-/outdoor)	2/-	2/2	2/-	2/2
Weight	12169,52 ft	11816,78 lbs	11419,95 lbs	12522,26 lbs
Total length	9,84 ft	10,76 ft	9,84 ft	10,76 ft
Total width	4,00 ft	4,00 ft	4,00 ft	4,00 ft
Total height - stowed	9,71 ft	9,71 ft	10,30 ft	10,30 ft
Transport height (rails folded)	7,05 ft	7,05 ft	7,64 ft	7,64 ft
Turning radius - outside	9,28 ft	10,30 ft	9,28 ft	10,30 ft
Ground clearance - center	0,89 ft	0,89 ft	0,89 ft	0,89 ft
Gradeability	25 %	25 %	25 %	25 %
Perm. tilt angle (long-/lat. axis)	1,5°/1,5°	1,5°(0,3°supp.)	1,5°/1,5°	1,5°(0,3°supp.)
Motor	8 kW 48V	8 kW 48V	8 kW 48V	8 kW 48V
Battery capacity	336Ah5 Aqua.	336Ah5 Aqua.	336Ah5 Aqua.	336Ah5 Aqua.

Technical data are subject to change.

PB TOP 12 series	PB S195-12E	PB S195-12ES	PB S225-12E	PB S225-12ES
Operation area	Indoor	In-/outdoor	Indoor	In-/outdoor
Drive	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic	Electro-hydraulic
Working height	64,30 ft	64,30 ft	73,82 ft	73,82 ft
Platform height - raised	57,74 ft	57,74 ft	67,26 ft	67,26 ft
Drivable at full height	Yes	Yes	Yes	Yes
Drive speed stowed / raised	1,01 / 0,06 mph	1,01 / 0,06 mph	1,01 / 0,06 mph	1,01 / 0,06 mph
Platform size (l x w)	12,53 x 3,90 ft	12,53 x 3,90 ft	13,06 x 3,90 ft	13,06 x 3,90 ft
Platform size max. (l x w)	17,45 x 3,90 ft	17,45 x 3,90 ft	17,98 x 3,90 ft	17,98 x 3,90 ft
Lift capacity	1543,24 lbs	1543,24 lbs	1322,77 lbs	1322,77 lbs
Lift capacity extension	1543,24 lbs	1543,24 lbs	1322,77 lbs	1322,77 lbs
Occupancy (in-/outdoor)	2/-	2/2	2/-	2/2
Weight	ca. 21274,61 lbs	21936 lbs	ca. 22046,23 lbs	22685,57 lbs
Total length	13,71 ft	14,80 ft	13,71 ft	14,83 ft
Total width	4,00 ft	4,00 ft	4,00 ft	4,00 ft
Total height - stowed	11,35 ft	11,35 ft	11,71 ft	11,71 ft
Transport height (rails folded)	8,04 ft	8,04 ft	8,96 ft	8,96 ft
Turning radius - outside	11,98 ft	11,98 ft	11,98 ft	11,98 ft
Ground clearance - center	0,89 ft	0,89 ft	0,89 ft	0,89 ft
Gradeability	25 %	25 %	25 %	25 %
Perm. tilt angle (long-/lat. axis)	1,5°/1,5°	1,5°(0,3°supp.)	1,5°/1,5°	1,5°(0,3°supp.)
Motor	2x 8 kW 48V	2x 8 kW 48V	2x 8 kW 48V	2x 8 kW 48V
Battery capacity	640Ah5 Aqua.	640Ah5 Aqua.	640Ah5 Aqua.	640Ah5 Aqua.

Technical data are subject to change.

Technical highlights in series

- No space? no problem:
Slim + extremely high
- Auto. PB supports system
 - Differential lock
- Emission-free & eco-friendly & reliable



According and compliant to standards: ANSI/SAIA A92.20; CAN/CSA-B354.6; DIN EN 280-1; AS/NZS 1418.10